



Boring bar steel, left-hand, Shank \varnothing / insert size: 10/07 mm



Order data

Order number	261357 10/07
GTIN	4062406285739
Item class	21T

Description

Boring bar steel 10/07 mm ISO code toolholder: A10H SVXCR/L07

Setting angle κ : 113 degrees

suitable indexable insert: VC.. 0702..

Minimum pre-drill $\varnothing D_{\min}$: 12.5 mm

Centre-line offset: 7 mm

Clamping height H: 9 mm

Technical description

Free length	32 mm
Minimum pre-drill $\varnothing D_{\min}$	12.5 mm
Shank \varnothing	10 mm
Pack of insert screws	269435 3
Neck width	6.8 mm
Setting angle κ	113 degrees
Overall length L	100 mm
Overhang L_1 recessed holders	22 mm
ISO code toolholder	A10H SVXCR/L07
Centre-line offset	7 mm
suitable indexable insert	VC.. 0702..
Clamping height H	9 mm

Insert size	7 mm
Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Shank type	Boring bar
Application	Internal longitudinal turning
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces Type 3	269435 3
---------------------------------------	----------