



Boring bar steel, left-hand, Shank \varnothing / insert size: 8/05 mm



Order data

Order number	261357 8/05
GTIN	4062406285722
Item class	21T

Description

Boring bar steel 8/05 mm ISO code toolholder: A08F SVXCR/L05

Setting angle κ : 113 degrees

suitable indexable insert: VC.. 0501..

Minimum pre-drill $\varnothing D_{\min}$: 9.2 mm

Centre-line offset: 5 mm

Clamping height H: 7.5 mm

Technical description

Overall length L	80 mm
Free length	15 mm
Setting angle κ	113 degrees
Overhang L_1 recessed holders	15 mm
ISO code toolholder	A08F SVXCR/L05
suitable indexable insert	VC.. 0501..
Centre-line offset	5 mm
Minimum pre-drill $\varnothing D_{\min}$	9.2 mm
Pack of insert screws	269435 2
Shank \varnothing	8 mm
Insert size	5 mm
Clamping height H	7.5 mm

Neck width	6 mm
Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Shank type	Boring bar
Application	Internal longitudinal turning
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces Type 2	269435 2
---------------------------------------	----------