

Garant

Boring bar carbide, left-hand, Shank \varnothing / insert size: 8/05 mm



Order data

Order number	261369 8/05
GTIN	4062406285883
Item class	21T

Description

Boring bar carbide 8/05 mm Shank \varnothing D_3 : 8 mm
 ISO code toolholder: E08F SVXCR/L05
 Setting angle κ : 113 degrees
 suitable indexable insert: VC.. 0501..
 Minimum pre-drill \varnothing D_{min} : 9.2 mm
 Centre offset L_3 : 5 mm

Technical description

Centre offset L_3	5 mm
Overall length L	80 mm
suitable indexable insert	VC.. 0501..
Minimum pre-drill \varnothing D_{min}	9.2 mm
ISO code toolholder	E08F SVXCR/L05
Pack of insert screws	269028 27
Head length L_1	26 mm
Insert size	5 mm
Setting angle κ	113 degrees
Neck width L_4	6 mm
Clamping height L_2	7.5 mm
Usable depth T	3 mm

Shank $\varnothing D_s$	8 mm
Application type	left-hand
Boring depth up to	8xD
Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 26	269028 26
------------------------------	-----------