

Garant
Cutting head, right-hand, System / insert size: GL/10

Order data

| | |
|--------------|---------------|
| Order number | 264830 GL/10 |
| GTIN | 4062406231439 |
| Item class | 29D |

Description
Suitable for :

Boring bar shanks No. 264866 / 4870.

Note:

Combination of all GL system interchangeable cutting heads with all GL system boring bar shanks is possible.

Through-coolant: yes

System: GL

Cutting point / joint: 16 mm

ISO code indexable cutting head: SCLCR

suitable indexable insert: CC.. 0602..

Approach angle: 95 degrees

Minimum pre-drill $\varnothing D_{\min}$: 20 mm

Centre offset L_3 : 11 mm

Technical description

| | |
|------------------|------------|
| Overall length L | 15.4 mm |
| Approach angle | 95 degrees |

| | |
|--|--------------|
| ISO code indexable cutting head | SCLCR |
| Centre offset L ₃ | 11 mm |
| Cutting point / joint | 16 mm |
| suitable indexable insert | CC.. 0602.. |
| Insert screw | 269028 38 |
| System | GL |
| Minimum pre-drill $\varnothing D_{\min}$ | 20 mm |
| Application type | right-hand |
| Through-coolant | yes |
| Type of product | Cutting head |

Accessories

| | |
|------------------------------|-----------|
| Set of insert screws Type 38 | 269028 38 |
|------------------------------|-----------|