

Cutting head, right-hand, System / insert size: DM/40**Order data**

Order number	264838 DM/40
GTIN	4251414902442
Item class	29D

Description**Version:**

Interchangeable cutting heads for **vibration-damping base bodies**.

Suitable for :

Boring bar shanks No. 264910 / 4930 / 4934.

Note:

All DM system interchangeable cutting heads can be combined with all DM system boring bar shanks (irrespective of shank -Ø).

Through-coolant: yes

System: DM

Cutting point / joint: 40 mm

ISO code indexable cutting head: DCLNR

suitable indexable insert: CN.. 1204..

Approach angle: 95 degrees

Minimum pre-drill Ø D_{min}: 48 mm

Centre offset L₃: 27 mm

Technical description

Minimum pre-drill Ø D _{min}	48 mm
--------------------------------------	-------

Overall length L	35 mm
Approach angle	95 degrees
Shim	259033 2
Shim screw	259027 2
suitable indexable insert	CN.. 1204..
ISO code indexable cutting head	DCLNR
Clamp, screw, O-ring	259036 3
Centre offset L ₃	27 mm
System	DM
Cutting point / joint	40 mm
Application type	right-hand
Through-coolant	yes
Type of product	Cutting head

Accessories

Shim screw	259612
Shim	259224
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX10	674248 TX10
Clamp unit	259505
Clamp unit Type 3	259036 3
Shim Type 2	259033 2
Shim screw 10 pieces Type 2	259027 2