

Cutting head, right-hand, System / insert size: DM/45



Order data

Order number	264838 DM/45
GTIN	4251414903005
Item class	29D

Description

Version:

Interchangeable cutting heads for **vibration-damping base bodies**.

Suitable for :

Boring bar shanks No. 264910 / 4930 / 4934.

Note:

All DM system interchangeable cutting heads can be combined with all DM system boring bar shanks (irrespective of shank - \varnothing).

Through-coolant: yes

System: DM

Cutting point / joint: 40 mm

ISO code indexable cutting head: DWLNR

suitable indexable insert: WN.. 0804..

Approach angle: 95 degrees

Minimum pre-drill $\varnothing D_{\min}$: 48 mm

Centre offset L_3 : 27 mm

Technical description

Approach angle	95 degrees
----------------	------------

System	DM
Overall length L	35 mm
Minimum pre-drill $\varnothing D_{\min}$	48 mm
Cutting point / joint	40 mm
Clamp, screw, O-ring	259036 3
Shim screw	259027 4
Shim	259033 6
suitable indexable insert	WN.. 0804..
Centre offset L ₃	27 mm
ISO code indexable cutting head	DWLNR
Application type	right-hand
Through-coolant	yes
Type of product	Cutting head

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Clamping screw	269406
Clamp unit Type 5	259036 5
Shim Type 6	259033 6
Clamping screw Type 3	269022 3
Shim screw 10 pieces Type 4	259027 4