

Cutting head, right-hand, System / insert size: DM/49



Order data

Order number	264838 DM/49
GTIN	4251414902701
Item class	29D

Description

Version:

Interchangeable cutting heads for **vibration-damping** base bodies.

Suitable for :

Boring bar shanks No. 264910; 264930 and 264934.

Note:

All DM system interchangeable cutting heads can be combined with all DM system boring bar shanks (irrespective of shank dia).

Through-coolant: yes

System: DM

Cutting point / joint: 40 mm

ISO code indexable cutting head: STUCR

suitable indexable insert: TC.. 16T3..

Approach angle: 93 degrees

Minimum pre-drill $\varnothing D_{\min}$: 49 mm

Centre offset L_3 : 27 mm

Technical description

Cutting point / joint	40 mm
-----------------------	-------

ISO code indexable cutting head	STUCR
Insert screw	269023 3
System	DM
Centre offset L ₃	27 mm
Shim	259033 4
Approach angle	93 degrees
Shim screw	269015 2
Overall length L	32 mm
Minimum pre-drill Ø D _{min}	49 mm
suitable indexable insert	TC.. 16T3..
Application type	right-hand
Through-coolant	yes
Type of product	Cutting head

Accessories

Clamping screw Type 3	269023 3
Clamping screw	269433
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15