

Cutting head, left-hand, System / insert size: DM/43**Order data**

Order number	264839 DM/43
GTIN	4251414902879
Item class	29D

Description**Version:**

Interchangeable cutting heads for **vibration-damping base bodies**.

Suitable for :

Boring bar shanks No. 264910 / 4930 / 4934.

Note:

All DM system interchangeable cutting heads can be combined with all DM system boring bar shanks (irrespective of shank -Ø).

Through-coolant: yes

System: DM

Cutting point / joint: 40 mm

ISO code indexable cutting head: DTUNL

suitable indexable insert: TN.. 1604..

Approach angle: 93 degrees

Minimum pre-drill Ø D_{min}: 48 mm

Centre offset L₃: 27 mm

Technical description

Cutting point / joint	40 mm
-----------------------	-------

System	DM
Shim screw	259027 1
Shim	259033 4
Minimum pre-drill Ø D _{min}	48 mm
Centre offset L ₃	27 mm
Approach angle	93 degrees
Clamp, screw, O-ring	259036 6
suitable indexable insert	TN.. 1604..
ISO code indexable cutting head	DTUNL
Overall length L	35 mm
Application type	left-hand
Through-coolant	yes
Type of product	Cutting head

Accessories

Shim screw	259611
Shim	259226
Clamp unit	259508
Shim screw 10 pieces Type 1	259027 1
Clamp unit Type 6	259036 6
Shim Type 4	259033 4