

Garant
DCGW 04T001 FN, PCD, Cutting edge version: N

Order data

Order number	265829 N
GTIN	4062406561123
Item class	21L

Description
Version:

PCD – Polycrystalline diamond, fine grain. Neutral, without chip breaker.

Application:

For aluminium, aluminium alloys, non-ferrous metals, plastics, composite materials, titanium alloys, sintered metals.

Grade: PCD

Chip breaker: FN

Cutting edge version: N

Cutting depth a_p : 0.1 - 2.5 mm

Feed f : 0.03 - 0.4 mm/rev.

Cutting speed v_c for alu < 10 % Si: 300 - 2000 m/min

Technical description

Cutting depth a_p	0.1 - 2.5 mm
Feed f	0.03 - 0.4 mm/rev.
Cutting conditions	continuous

Number of changes/inserts	1
Cutting speed v_c for G(C)RP	150 - 600 m/min
ISO code indexable insert	DCGW 04T001 FN
Cutting speed v_c for alu < 10 % Si	300 - 2000 m/min
Grade	PCD
Chip breaker	FN
Cutting edge version	N
Cutting speed v_c for non-ferrous metals	300 - 1500 m/min
Tool material	PCD
Corner radius	0.1 mm
Finishing/roughing assignment	Semi-roughing
Product name attribute	PCD
Rake	0 degrees
Type of product	Indexable insert for turning