

Garant

"4 in 1" drilling and turning tool 2.25×D, right-hand, Ø DC: 25 mm


Order data

Order number	268408 25
GTIN	4062406392635
Item class	21X

Description
Version:

Plain shank **with collar.**

Application:

1. Facing of end faces.
2. Drilling (drilling out and drilling from solid) – flat drilled hole end.
3. Internal longitudinal turning.
4. External longitudinal turning.

Note:

- **Choose corner radii and toolholder size as large as possible.**
- **Drilling tolerance + 0.15 mm (for drilling processes with a driven tool).**
- **When drilling greater than nominal Ø, residual material will remain.**
- **Always use internal cooling for drilling (at least 5 bar).**

Through-coolant: yes

Overhang L_A : 73 mm

Shank length L_s : 60 mm

Reach L_1 : 56 mm

Shank Ø D_s : 32 mm

Ø d_2 : 40 mm

suitable indexable insert: ZCMX 13..

Technical description

Shank length L_s	60 mm
suitable indexable insert	ZCMX 13..
Reach L_1	56 mm

Shank Ø D _s	32 mm
Pack of insert screws	269028 45 (IP20; 5 Nm)
Nominal Ø D	25 mm
Ø d ₂	40 mm
Overhang L _A	73 mm
Application type	right-hand
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 43	269028 43
Set of insert screws Type 45	269028 45