

## Garant

### Profile slotting toolholder for square cutting inserts $\varnothing$ D1 32 mm, from square: 17 mm



#### Order data

Order number	290334 17
GTIN	4062406352295
Item class	21U

#### Description

##### Note:

- **For machining centres, use the alignment aid No. 290397 and a dial indicator to check the spindle orientation.**
- **For lathes without Y-axis, please use eccentric bush No. 290391– 290393 for exact setting of the Y-coordinate.**

Through-coolant: yes

Shank length  $L_3$ : 100 mm

suitable for square drive: 17 - 19 mm

Reach  $L_1$ : 52 mm

Tool holder  $\varnothing$   $D_2$ : 16 mm

Centre offset  $L_3$ : 8.5 mm

Min. pre-drilling  $-\varnothing$   $D_{\min}$ : 17.2 mm

Screw: 290399 3

#### Technical description

Reach $L_1$	52 mm
Tool holder $\varnothing$ $D_2$	16 mm
Min. pre-drilling $-\varnothing$ $D_{\min}$	17.2 mm
Screw	290399 3
suitable for square drive	17 - 19 mm
Centre offset $L_3$	8.5 mm

Shank Ø	25 mm
Through-coolant	yes
Shank length L <sub>s</sub>	100 mm
Shank	Combination shank
Type of product	Keyway broaching and profile slotting tools