

duMONT

Keyway push broach HSS Fit P9, Type: 8C1



Order data

Order number	290406 8C1
GTIN	662600888060
Item class	29 J

Description

Application:

For production of keyways to DIN 6885.

Supplied with:

Broaches including the necessary shims.

Note:

- · Broaches for high tensile materials, increased number of passes or special applications available (on request).
- · After first and second of three passes, back the broach off slightly the broach will then align itself.
- · Coated broaches and inch size broaches available on request.
- BROACHING PRESSES can be found in Volume 2 (Hand tools and metrology).
- · Size 28; 32 and 36 available on request, on short lead times.

Tool material: HSS Broach length: 299 mm Keyway width: 8 mm Keyway depth: 3.3 mm

for bore Ø to DIN 6885: 22 - 30 mm Broaching length in steel: 10 - 64 mm

necessary broaching force for St50 and max. broaching length: 1700 kg



Technical description

Broaching length in steel	10 - 64 mm
for bore Ø to DIN 6885	22 - 30 mm
Back width	9.63 mm
Keyway depth	3.3 mm
Number of passes	3
Broach length	299 mm
Keyway width	8 mm
necessary broaching force for St50 and max. broaching length	1700 kg
Tool material	HSS
Type of product	Broach

Accessories

Shim for push broach No. 290405 – 407 Type 8C1	290410 8C1
--	------------