



## Side lock arbor Form AD with cooling channel bores, SK 40 short, Clamping range $\varnothing$ D1: 25 mm



### Order data

Order number	300225 25
GTIN	4062406242671
Item class	32A

### Description

#### Version:

With Balluffchip bore.

All shanks fine bead blasted. Balancing quality G 6.3 / 18,000 rpm.

**With cooling channel bores. Cannot be plugged.**

#### Description:

Balancing quality G 6.3 / 18,000 rpm.

#### Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

#### Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 100 mm

External  $\varnothing$  D: 65 mm

Spare clamping screw No. 30 9900: 25

### Technical description

External $\varnothing$ D	65 mm
Overhang dimension A	100 mm
Clamping $\varnothing$ D <sub>1</sub>	25 mm
Spare clamping screw No. 30 9900	25
Adapter	SK 40 short

Standard	DIN 6359
Arbor standard	DIN 69871
Arbor standard	ISO 7388-1
Shape	AD
Cooling channel bore	not pluggable
Balance quality G at rotational speed	G 6.3 at 18,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HPC
Type of product	Side lock arbor