

**Side lock arbor Form AD, SK 50 short, Clamping range Ø D₁: 18 mm****Order data**

Order number	300315 18
GTIN	4062406243029
Item class	32A

Description**Version:**

With Balluffchip bore.

All shanks fine bead blasted. Balancing quality G 6.3 / 18,000 rpm.

Description:

Balancing quality G 6.3 / 18,000 rpm.

Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Machining strategy: HPC

Overhang dimension A: 63 mm

External Ø D: 50 mm

Spare clamping screw No. 30 9900: 16

Technical description

Overhang dimension A	63 mm
External Ø D	50 mm
Spare clamping screw No. 30 9900	16
Clamping Ø D ₁	18 mm
Adapter	SK 50 short

Standard	DIN 6359
Arbor standard	ISO 7388-1
Shape	AD
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Spare clamping screw for chucks with clamping $\varnothing$ D1 16 mm	309900 16
--	-----------