



Side lock arbor Form AD, SK 50 short, Clamping range $\varnothing D_1$: 6 mm



Order data

Order number	300315 6
GTIN	4062406242961
Item class	32A

Description

Version:

With Balluffchip bore.

All shanks fine bead blasted. Balancing quality G 6.3 / 18,000 rpm.

Description:

Balancing quality G 6.3 / 18,000 rpm.

Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Machining strategy: HPC

Overhang dimension A: 63 mm

External $\varnothing D$: 25 mm

Spare clamping screw No. 30 9900: 6

Technical description

External $\varnothing D$	25 mm
Clamping $\varnothing D_1$	6 mm
Overhang dimension A	63 mm
Spare clamping screw No. 30 9900	6
Adapter	SK 50 short

Standard	DIN 6359
Arbor standard	ISO 7388-1
Shape	AD
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Spare clamping screw for chucks with clamping Ø D1 6 mm

309900 6