



## Side lock arbor Form AD, SK 50 short, Clamping range $\varnothing$ D1: 8 mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 300315 8      |
| GTIN         | 4062406242978 |
| Item class   | 32A           |

### Description

#### Version:

With Balluffchip bore.

All shanks fine bead blasted. Balancing quality G 6.3 / 18,000 rpm.

#### Description:

Balancing quality G 6.3 / 18,000 rpm.

#### Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

#### Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 63 mm

External  $\varnothing$  D: 28 mm

Spare clamping screw No. 30 9900: 8

### Technical description

|                                       |             |
|---------------------------------------|-------------|
| Clamping $\varnothing$ D <sub>1</sub> | 8 mm        |
| External $\varnothing$ D              | 28 mm       |
| Spare clamping screw No. 30 9900      | 8           |
| Overhang dimension A                  | 63 mm       |
| Adapter                               | SK 50 short |

|                                       |                      |
|---------------------------------------|----------------------|
| Standard                              | DIN 6359             |
| Arbor standard                        | ISO 7388-1           |
| Arbor standard                        | DIN 69871            |
| Shape                                 | AD                   |
| Balance quality G at rotational speed | G 6.3 at 15,000 rpm  |
| Concentricity                         | $\leq 3 \mu\text{m}$ |
| Machining strategy                    | HPC                  |
| Type of product                       | Side lock arbor      |