



Side lock arbor Form AD with cooling channel bores, SK 50 short, Clamping range \varnothing D1: 40 mm



Order data

| | |
|--------------|---------------|
| Order number | 300325 40 |
| GTIN | 4062406243173 |
| Item class | 32A |

Description

Version:

With Balluffchip bore.

All shanks fine bead blasted. Balancing quality G 6.3 / 18,000 rpm.

With cooling channel bores. Cannot be plugged.

Description:

Balancing quality G 6.3 / 18,000 rpm.

Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 120 mm

External \varnothing D: 80 mm

Spare clamping screw No. 30 9900: 32

Technical description

| | |
|---------------------------------------|--------|
| External \varnothing D | 80 mm |
| Spare clamping screw No. 30 9900 | 32 |
| Overhang dimension A | 120 mm |
| Clamping \varnothing D ₁ | 40 mm |

| | |
|---------------------------------------|----------------------|
| Adapter | SK 50 short |
| Standard | DIN 6359 |
| Arbor standard | DIN 69871 |
| Arbor standard | ISO 7388-1 |
| Shape | AD |
| Cooling channel bore | not pluggable |
| Balance quality G at rotational speed | G 6.3 at 18,000 rpm |
| Concentricity | $\leq 3 \mu\text{m}$ |
| Machining strategy | HPC |
| Type of product | Side lock arbor |