


**Side lock arbor Form AD, SK 50 A = 100, Clamping range  $\varnothing$  D<sub>1</sub>: 10 mm**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 300335 10     |
| GTIN         | 4062406243203 |
| Item class   | 32A           |

**Description**
**Version:**

With Balluffchip bore.

All shanks fine bead blasted. Balancing quality G 6.3 / 18,000 rpm.

**Description:**

Balancing quality G 6.3 / 18,000 rpm.

**Application:**

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

**Optional extras:**

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Machining strategy: HPC

External  $\varnothing$  D: 35 mm

Spare clamping screw No. 30 9900: 10

**Technical description**

|                                       |               |
|---------------------------------------|---------------|
| Clamping $\varnothing$ D <sub>1</sub> | 10 mm         |
| Spare clamping screw No. 30 9900      | 10            |
| External $\varnothing$ D              | 35 mm         |
| Adapter                               | SK 50 A = 100 |
| Standard                              | DIN 6359      |
| Arbor standard                        | ISO 7388-1    |

|                                       |                     |
|---------------------------------------|---------------------|
| Shape                                 | AD                  |
| Balance quality G at rotational speed | G 6.3 at 18,000 rpm |
| Concentricity                         | ≤ 3 μm              |
| Machining strategy                    | HPC                 |
| Type of product                       | Side lock arbor     |

---

## Accessories

|  |           |
|--|-----------|
| Spare clamping screw for chucks with clamping Ø D1 10 mm | 309900 10 |
|--|-----------|