

**Side lock arbor Form AD, SK 50 A = 160, Clamping range Ø D1: 8 mm****Order data**

Order number	300355 8
GTIN	4062406243272
Item class	32A

Description**Version:**

With Balluffchip bore.

All shanks fine bead blasted. Balancing quality G 6.3 / 18,000 rpm.

Description:

Balancing quality G 6.3 / 18,000 rpm.

Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Machining strategy: HPC

External Ø D: 28 mm

Spare clamping screw No. 30 9900: 8

Technical description

Clamping Ø D ₁	8 mm
External Ø D	28 mm
Spare clamping screw No. 30 9900	8
Adapter	SK 50 A = 160
Standard	DIN 6359
Arbor standard	ISO 7388-1

Shape	AD
Balance quality G at rotational speed	G 6.3 at 18,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Spare clamping screw for chucks with clamping $\varnothing$ D1 8 mm	309900 8
---	----------