

Garant**Heavy-duty chuck with security function, SK 50, Ø D1: 12 mm****Order data**

Order number	300767 12
GTIN	4062406261214
Item class	31A

Description**Version:**

- Shanks hard turned (smooth cutting action).
- Very high clamping force prolongs tool life and improves surface quality.
- Centred tool clamping with optimum concentricity.
- Integral length adjustment screw.
- Internal coolant feed.

Advantage:

HB (Weldon) flat provides quick and easy protection against the milling cutter pulling out. Positive connection between the milling cutter and arbor. Compact vibration-optimised contour.

Application:

For clamping tools with parallel shank and HB flat. Ideally suited for heavy-duty machining (HPC, TPC).

Supplied with:

Clamping nut.

Overhang dimension A: 74 mm

Collet outer Ø D: 40 mm

Clamping force up to: 430 Nm

Suitable C-hook (pin) spanner No. 628400: 40/42

Technical description

Collet outer Ø D	40 mm
Suitable C-hook (pin) spanner No. 628400	40/42

Overhang dimension A	74 mm
Clamping Ø D ₁	12 mm
Clamping force up to	430 Nm
Adapter	SK 50
Arbor standard	ISO 7388-1
Arbor standard	DIN 69871
Shape	AD
Through-coolant	yes
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HPC
Type of product	Heavy-duty chuck

Accessories

C-hook (pin) spanner with square pin for external nut Ø 40/42 mm

628400 40/42