

Garant

Collet chuck, extra slim, with internal cooling, SK 40 A = 160, Clamping range: 2-6 mm

**Order data**

Order number	300786 2-6
GTIN	4062406256036
Item class	31A

Description**Version:**

- Taper ground internally and externally.
- Shanks hard turned.
- With Balluffchip bore.
- The collet is clamped by a threaded connection from behind through the chuck, no clamping nut required.

Advantage:

Extremely slim design permits machining of components where access is difficult, e.g. for toolmaking and mould-making.

Application:

For clamping tools with plain shank to DIN 6499.

Supplied with:

Clamping screw and wrench with T-handle.

Optional extras:

Pull studs (PS) No. 308600 – 308806,

PS wrenches No. 308820 – 308835,

GARANT collets No. 309563,

ALBRECHT collets No. 309572 – 309573.

Machining strategy: HSC

Ø D₁: 9.6 mm

Ø D₂: 13 mm

External Ø D: 27 mm

Technical description

Clamping range	2 - 6 mm
Ø D ₁	9.6 mm
External Ø D	27 mm
Ø D ₂	13 mm
Adapter	SK 40 A = 160
Arbor standard	ISO 7388-1
Shape	AD
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HSC
Balluffchip bore	yes
Type of product	Collet chuck