

**Combination face mill adapter Form A, SK 40 short, Spigot Ø d1: 32 mm****Order data**

Order number	300837 32
GTIN	4062406251741
Item class	32A

Description**Version:**

Taper shank, spigot, and all contact surfaces ground at the collar. With Balluffchip bore.
All shanks fine bead blasted.

Application:

- **With drive key for mills with longitudinal keyway, e. g. DIN 841.**
- **With face mill drive ring for face mills with cross keyway, DIN 1880 and cutter heads to DIN 1830.**

Supplied with:

Drive key, face mill drive ring, and lock screw.

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840.

Overhang dimension A: 60 mm

External Ø D: 58 mm

Milling mandrel length L₃ with drive ring: 24 mm

Milling mandrel length L₄: 38 mm

Spare milling cutter lock screw No. 309860: 32

Spare drive ring No. 309870: 32

Technical description

Overhang dimension A	60 mm
Spare milling cutter lock screw No. 309860	32

External Ø D	58 mm
Milling mandrel length L ₄	38 mm
Milling mandrel length L ₃ with drive ring	24 mm
Suitable toggle spanner No. 309840	32
Spare drive ring No. 309870	32
Spigot Ø d ₁	32 mm
Adapter	SK 40 short
Standard	DIN 6358
Arbor standard	DIN 69871
Arbor standard	DIN 69871
Shape	A
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling cutter spigot

Accessories

Toggle spanner for mandrel Ø 32 mm	309840 32
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for steep tapers 50 SK	308820 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Milling cutter lock screw for mandrel Ø 32 mm	309860 32
Pull stud 45° sealed suitable for steep tapers 50	308765 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50
Pull stud Form A suitable for steep tapers 50	308600 50
Pull stud stud sealed, form A suitable for steep tapers 50	308610 50
Special pull stud with internal thread suitable for steep tapers 50	308740 50

Pull stud 45° sealed suitable for steep tapers 50	308760 50
Wrench for pull studs ISO 7388 suitable for steep tapers 50 SK	308830 50
Pull stud sealed suitable for steep tapers 50	308660 50
Face mill drive ring for mandrel Ø 32 mm	309870 32
Toggle spanner for mandrel Ø 50 mm	309840 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308700 50
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Milling cutter lock screw for mandrel Ø 50 mm	309860 50
Pull stud Form B suitable for steep tapers 50	308640 50
Torque insert for Pull studs to DIN 69872 suitable for steep tapers 50 SK	308810 50
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50	308605 50
Pull stud sealed, form B suitable for steep tapers 50	308650 50
Torque insert for Pull studs to SO 7388 suitable for steep tapers 50 SK	308812 50
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50	308615 50
Pull stud sealed, form B suitable for steep tapers 50	308620 50