

**Milling head arbor Form A, SK 40 short, Spigot Ø d1: 16 mm****Order data**

Order number	301017 16
GTIN	4062406251864
Item class	32A

Description**Version:**

- **From clamping Ø 40 with 4 tapped holes for face mills to DIN 2079.**
- **Taper shank, spigot, and all contact surfaces ground at the collar.**
- **Short series.**
- **Increased collar contact surface.**
- **With Balluffchip bore.**

All shanks fine bead blasted.

Supplied with:

Lock screw.

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840. Milling cutter lock screws No. 309860; 309861.

Machining strategy: HPC

Overhang dimension A: 35 mm

External Ø D: 38 mm

Milling mandrel length L₄: 17 mm

Spare milling cutter lock screw No. 309860 / 309861: 16

Suitable toggle spanner No. 309840: 16

Technical description

External Ø D	38 mm
Overhang dimension A	35 mm

Suitable toggle spanner No. 309840	16
Spare milling cutter lock screw No. 309860 / 309861	16
Spigot Ø d ₁	16 mm
Milling mandrel length L ₄	17 mm
Adapter	SK 40 short
Standard	DIN 6357
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HPC
Type of product	Milling head arbor