HOLEX

Milling head arbor Form A, SK 40 short, Spigot Ø d1: 32 mm



Order data

Order number	301017 32
GTIN	4062406251895
Item class	32A

Description

Version:
· **From clamping Ø 40 with 4 tapped holes for face mills to DIN 2079.**
· **Taper shank, spigot, and all contact surfaces ground at the collar.**
· **Short series.**
· **Increased collar contact surface.**
· **With Balluffchip bore.**
All shanks fine bead blasted.
Supplied with:
Lock screw.
Optional extras:
Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840. Milling cutter lock screws No. 309860; 309861.
Machining strategy: HPC
Overhang dimension A: 50 mm
External Ø D: 78 mm
Milling mandrel length L_4: 24 mm
Spare milling cutter lock screw No. 309860 / 309861: 32
Suitable toggle spanner No. 309840: 32

Technical description

Overhang dimension A	50 mm
Suitable toggle spanner No. 309840	32

Spare milling cutter lock screw No. 309860 / 309861	32
Milling mandrel length L_4	24 mm
Spigot ∅ d_1	32 mm
External ∅ D	78 mm
Adapter	SK 40 short
Standard	DIN 6357
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HPC
Type of product	Milling head arbor