

**Milling head arbor Form A, SK 40 short, Spigot Ø d1: 40 mm****Order data**

Order number	301017 40
GTIN	4062406251901
Item class	32A

Description**Version:**

- From clamping Ø 40 with 4 tapped holes for face mills to DIN 2079.
- Taper shank, spigot, and all contact surfaces ground at the collar.
- Short series.
- Increased collar contact surface.
- With Balluffchip bore.

All shanks fine bead blasted.

Supplied with:

Lock screw.

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840.

Overhang dimension A: 50 mm

External Ø D: 88 mm

Milling mandrel length L₄: 27 mm

Spare milling cutter lock screw No. 309860: 40

Technical description

External Ø D	88 mm
Spigot Ø d ₁	40 mm
Spare milling cutter lock screw No. 309860	40

Overhang dimension A	50 mm
Milling mandrel length L ₄	27 mm
Suitable toggle spanner No. 309840	40
Adapter	SK 40 short
Standard	DIN 6357
Arbor standard	DIN 69871
Arbor standard	DIN 69871
Shape	ADB
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HPC
Type of product	Milling head arbor