



Milling head arbor Form A, SK 40 short, Spigot Ø d1: 16 mm



Order data

Order number	301027 16
GTIN	4062406251918
Item class	32A

Description

Version:

- From clamping Ø 40 with 4 tapped holes for face mills to DIN 2079.
- Taper shank, spigot, and all contact surfaces ground at the collar.
- Short series.
- Increased collar contact surface.
- With Balluffchip bore.

All shanks fine bead blasted.

Supplied with:

Lock screw.

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840.

External Ø D: 38 mm

Milling mandrel length L₄: 17 mm

Spare milling cutter lock screw No. 309860: 16

Technical description

Spare milling cutter lock screw No. 309860	16
Milling mandrel length L ₄	17 mm
Spigot Ø d ₁	16 mm
Suitable toggle spanner No. 309840	16

External Ø D	38 mm
Adapter	SK 40 short
Standard	DIN 6357
Arbor standard	DIN 69871
Arbor standard	DIN 69871
Shape	ADB
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HPC
Type of product	Milling head arbor