



## Milling head arbor Form A, SK 40 short, Spigot $\varnothing$ d1: 32 mm



### Order data

Order number	301027 32
GTIN	4062406251949
Item class	32A

### Description

#### Version:

- From clamping  $\varnothing$  40 with 4 tapped holes for face mills to DIN 2079.
- Taper shank, spigot, and all contact surfaces ground at the collar.
- Short series.
- Increased collar contact surface.
- With Balluffchip bore.

All shanks fine bead blasted.

#### Supplied with:

Lock screw.

#### Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840.

External  $\varnothing$  D: 78 mm

Milling mandrel length  $L_4$ : 24 mm

Spare milling cutter lock screw No. 309860: 32

### Technical description

Milling mandrel length $L_4$	24 mm
Spigot $\varnothing$ d <sub>1</sub>	32 mm
External $\varnothing$ D	78 mm
Spare milling cutter lock screw No. 309860	32

Suitable toggle spanner No. 309840	32
Adapter	SK 40 short
Standard	DIN 6357
Arbor standard	DIN 69871
Arbor standard	DIN 69871
Shape	ADB
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	≤ 5 μm
Machining strategy	HPC
Type of product	Milling head arbor