



Milling head arbor Form A, SK 50 short, Spigot \varnothing d1: 32 mm



Order data

| | |
|--------------|---------------|
| Order number | 301097 32 |
| GTIN | 4062406251970 |
| Item class | 32A |

Description

Version:

- From clamping \varnothing 40 with 4 tapped holes for face mills to DIN 2079.
- Taper shank, spigot, and all contact surfaces ground at the collar.
- Short series.
- Increased collar contact surface.
- With Balluffchip bore.

All shanks fine bead blasted.

Supplied with:

Lock screw.

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840.

Overhang dimension A: 50 mm

External \varnothing D: 78 mm

Milling mandrel length L_4 : 24 mm

Spare milling cutter lock screw No. 309860: 32

Technical description

| | |
|-------------------------------------|-------|
| Spigot \varnothing d ₁ | 32 mm |
| Milling mandrel length L_4 | 24 mm |
| External \varnothing D | 78 mm |

| | |
|--|---------------------|
| Suitable toggle spanner No. 309840 | 32 |
| Spare milling cutter lock screw No. 309860 | 32 |
| Overhang dimension A | 50 mm |
| Adapter | SK 50 short |
| Standard | DIN 6357 |
| Arbor standard | DIN 69871 |
| Arbor standard | ISO 7388-1 |
| Shape | A |
| Balance quality G at rotational speed | G 6.3 at 18,000 rpm |
| Concentricity | ≤ 6 μm |
| Machining strategy | HPC |
| Type of product | Milling head arbor |