



## Milling head arbor Form A, SK 50 short, Spigot Ø d1: 40 mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 301097 40     |
| GTIN         | 4062406251987 |
| Item class   | 32A           |

### Description

#### Version:

- From clamping Ø 40 with 4 tapped holes for face mills to DIN 2079.
- Taper shank, spigot, and all contact surfaces ground at the collar.
- Short series.
- Increased collar contact surface.
- With Balluffchip bore.

All shanks fine bead blasted.

#### Supplied with:

Lock screw.

#### Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840.

Overhang dimension A: 50 mm

External Ø D: 89 mm

Milling mandrel length L<sub>4</sub>: 27 mm

Spare milling cutter lock screw No. 309860: 40

### Technical description

|                                    |       |
|------------------------------------|-------|
| External Ø D                       | 89 mm |
| Suitable toggle spanner No. 309840 | 40    |
| Spigot Ø d <sub>1</sub>            | 40 mm |

|  |                     |
|--|---------------------|
| Spare milling cutter lock screw No. 309860 | 40                  |
| Overhang dimension A                       | 50 mm               |
| Milling mandrel length L <sub>4</sub>      | 27 mm               |
| Adapter                                    | SK 50 short         |
| Standard                                   | DIN 6357            |
| Arbor standard                             | DIN 69871           |
| Arbor standard                             | ISO 7388-1          |
| Shape                                      | A                   |
| Balance quality G at rotational speed      | G 6.3 at 18,000 rpm |
| Concentricity                              | ≤ 6 μm              |
| Machining strategy                         | HPC                 |
| Type of product                            | Milling head arbor  |