

Garant

High-Performance milling head arbor vibration-damped, cylindrical with cooling channel bores, SK 50 A = 200, Spigot Ø d1: 22 mm


Order data

Order number	301103 22
GTIN	4045197946201
Item class	31H

Description
Version:

- Shank, spigot, and all contact surfaces are ground at the collar.
- With Balluffchip bore.
- Larger collar contact face.
- Vibration damped version, arbor with vibration-damping core.

Advantage:

The heavy metal core specially matched to the arbors gives optimum machining results even with long overhangs:

- Saves time, because allows use of the maximum machining parameters.
- Smooth running and thus perfect surface quality results.
- Saves costs, because tool life is increased.
- Less vibrational stress on the machine headstock.

Supplied with:

Cutter lock screw and drive dog.

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, Special toggle spanner No. 309840.

Note:

Balance quality G 6.3 dependent on the maximum operating speed.

External Ø D: 48 mm

Milling mandrel length L₄: 19 mm

maximum speed n_{max}: 8000 rpm

Technical description

External Ø D	48 mm
--------------	-------

Spigot Ø d ₁	22 mm
Milling mandrel length L ₄	19 mm
maximum speed n _{max}	8000 rpm
Adapter	SK 50 A = 200
Standard	DIN 6357
Arbor standard	DIN 69871
Arbor standard	ISO 7388-1
Shape	AD
Balance quality G at rotational speed	G 6.3 at 8,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HPC
Vibration	damped
Type of product	Milling head arbor