

Garant
Intermediate sleeve, SK 40, Short taper SK / SK 1: 40/40

Order data

Order number	301272 40/40
GTIN	4062406105105
Item class	31A

Description
Supplied with:

With built-in connecting screw for arbors according to ISO 7388-1. (Formerly DIN 69871)

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Concentricity: $\leq 5 \mu\text{m}$

Overhang dimension A: 100 mm

External \varnothing D: 63 mm

Technical description

Overhang dimension A	100 mm
External \varnothing D	63 mm
Adapter	SK 40
Arbor standard	ISO 7388-1
Shape	A
Balance quality G at rotational speed	G 2.5 at 15,000 rpm
Concentricity	$\leq 5 \mu\text{m}$
Type of product	Arbor adapter

Accessories

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308630 40
ER chuck key 1/2 inch socket for ER collet chuck 40	309700 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Pull stud sealed, form B suitable for steep tapers 40	308620 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud sealed suitable for steep tapers 40	308660 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Pull stud sealed, form B suitable for steep tapers 40	308650 40
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40	308615 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud Mazak sealed, form A suitable for steep tapers 40M	308670 40M
Special pull stud with no internal thread sealed suitable for steep tapers 40	308720 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Pull stud sealed suitable for steep tapers 40	308635 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40

Pull stud Form B suitable for steep tapers 40	308640 40
Torque wrench with reversible ratchet maximum torque 200 Nm	656050 200
Pull stud 60° sealed suitable for steep tapers 40	308785 40
ER chuck key for ER collet chuck 40	309680 40
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Special pull stud with no internal thread sealed suitable for steep tapers 40	308700 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40