

Garant**Arbor for indexable drills Form ADB, SK 50, for shank Ø D1: 40 mm****Order data**

Order number	301287 40
GTIN	4062406105013
Item class	31A

Description**Version:**

- **Position of the threaded pin for countersinking in the indexable drill offset by 0.4 mm.**
- **When tightening the increased contact face Ø is clamped against the front face of the arbor.**
- **Better support, allowing higher feed rates.**
- **High concentricity thanks to the mating surface being ground flat to 3µm.**
- **With Balluffchip bore.**

Callout:

Indexable drill

Toolholder

Ground contact face

Form ADB

Application:**For mounting all standard indexable drills to DIN 6595, Part 1.****Suitable for :**

All indexable drills with parallel shank to DIN 6595, Part 1.

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835, replacement screws No. 309907, 309908.

Overhang dimension A: 80 mm

External Ø D: 60 mm

Technical description

External Ø D	60 mm
Overhang dimension A	80 mm
Adapter	SK 50
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Type of product	Indexable drill head adapter

Accessories

Torque insert for Pull studs to ISO 7388 suitable for ISO taper size 50	308812 50
Wrench for pull studs ISO 7388 suitable for ISO taper size 50	308830 50
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50	308820 50
Pull stud Form A suitable for steep tapers 50	308600 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Pull stud 45° sealed suitable for steep tapers 50	308760 50
ER chuck key 1/2 inch socket for ER collet chuck 40	309700 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50	308605 50
Pull stud sealed, form B suitable for steep tapers 50	308650 50
Pull stud sealed, form B suitable for steep tapers 50	308620 50
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308700 50
Pull stud Form B suitable for steep tapers 50	308640 50
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50

Special pull stud with internal thread suitable for steep tapers 50	308740 50
Pull stud 45° sealed suitable for steep tapers 50	308765 50
Pull stud sealed, form A suitable for steep tapers 50	308610 50
ER chuck key for ER collet chuck 40	309680 40
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Torque wrench with reversible ratchet maximum torque 200 Nm	656050 200
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50	308615 50
Pull stud sealed suitable for steep tapers 50	308660 50