



Boring bar blank Form A, SK 50, A dimension: 315 mm



Order data

Order number	301302 315
GTIN	4062406105037
Item class	32A

Description

Version:

Taper arbor and collar hardened and ground.

Material:

16 MnCr5

Optional extras:

Pull studs (PS) No. 308600 – 308806. Pull stud wrenches No. 308820; 308835.

Shape: A

External Ø D: 97 mm

Technical description

External Ø D	97 mm
Adapter	SK 50
Arbor standard	ISO 7388-1
Shape	A
Type of product	Boring bar blank

Accessories

Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50
---	-----------

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50	308820 50
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50	308605 50
Pull stud sealed suitable for steep tapers 50	308660 50
Pull stud sealed, form B suitable for steep tapers 50	308620 50
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Pull stud 45° sealed suitable for steep tapers 50	308760 50
Torque insert for Pull studs to ISO 7388 suitable for ISO taper size 50	308812 50
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
Pull stud 45° sealed suitable for steep tapers 50	308765 50
Pull stud sealed, form B suitable for steep tapers 50	308650 50
Torque wrench with reversible ratchet maximum torque 200 Nm	656050 200
Pull stud sealed, form A suitable for steep tapers 50	308610 50
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50	308615 50
Special pull stud with internal thread suitable for steep tapers 50	308740 50
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308700 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Pull stud Form B suitable for steep tapers 50	308640 50
Wrench for pull studs ISO 7388 suitable for ISO taper size 50	308830 50
Pull stud Form A suitable for steep tapers 50	308600 50