

Garant
Arbor for screw-in milling cutters with thread, SK 40, Thread M × Length L1: M16X75

Order data

Order number	301303 M16X75
GTIN	4062406105518
Item class	31A

Description
Version:

Tapered design.

Application:

To take screw-in milling cutters with thread.

Optional extras:

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835.

Machining strategy: HSC

Overhang dimension A: 94 mm

Bore $\varnothing D_1$ tolerance IT6: 17 mm

$\varnothing D_2$: 29 mm

External $\varnothing D$: 34 mm

Reach L_1 : 75 mm

L_2 : 5 mm

Technical description

Bore $\varnothing D_1$ tolerance IT6	17 mm
$\varnothing D_2$	29 mm
L_2	5 mm
Overhang dimension A	94 mm
Thread M	M16x75

External Ø D	34 mm
Reach L ₁	75 mm
Adapter	SK 40
Arbor standard	DIN 69871
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Type of product	Threaded copy mill arbor

Accessories

Pull stud Form B suitable for steep tapers 40	308640 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud sealed, form B suitable for steep tapers 40	308650 40
Pull stud stud sealed, form A suitable for steep tapers 40	308610 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for steep tapers 40 SK	308820 40
Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud sealed suitable for steep tapers 40	308635 40
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 40	308605 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Torque insert for Pull studs to SO 7388 suitable for steep tapers 40 SK	308812 40
Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
	308801 40

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40

Wrench for pull studs ISO 7388 suitable for steep tapers 40 SK

308830 40

Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 40

308615 40

ER chuck key for ER collet chuck 40

309680 40

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40

308802 40

Special pull stud with no internal thread sealed suitable for steep tapers 40

308700 40

Special pull stud with no internal thread sealed suitable for steep tapers 40

308720 40

Torque wrench with reversible ratchet maximum torque 200 Nm

656050 200

Torque insert for Pull studs to DIN 69872 suitable for steep tapers 40 SK

308810 40

Special pull stud with internal thread suitable for steep tapers 40

308740 40

Pull stud Mazak sealed, form A suitable for steep tapers 40M

308670 40M

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers 40

308630 40

Pull stud 45° sealed suitable for steep tapers 40

308765 40

ER chuck key 1/2 inch socket for ER collet chuck 40

309700 40

Pull stud sealed, form B suitable for steep tapers 40

308620 40

Pull stud Form A suitable for steep tapers 40

308600 40

Pull stud 90° sealed suitable for steep tapers 40

308790 40

Pull stud 45° sealed suitable for steep tapers 40

308760 40