

**Garant**
**Arbor for screw-in milling cutters with thread, SK 50, Thread M × Length L1:  
M10X150**

**Order data**

Order number	301304 M10X150
GTIN	4062406105570
Item class	31A

**Description**
**Version:**

Tapered design.

**Application:**

To take screw-in milling cutters with thread.

**Optional extras:**

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308820 – 308835.

Machining strategy: HSC

Overhang dimension A: 169 mm

Bore  $\varnothing D_1$  tolerance IT6: 10.5 mm

$\varnothing D_2$ : 18 mm

External  $\varnothing D$ : 36.5 mm

Reach  $L_1$ : 150 mm

$L_2$ : 10 mm

**Technical description**

Reach $L_1$	150 mm
$L_2$	10 mm
Thread M	M10×150
$\varnothing D_2$	18 mm
Overhang dimension A	169 mm

External Ø D	36.5 mm
Bore Ø D <sub>1</sub> tolerance IT6	10.5 mm
Adapter	SK 50
Arbor standard	ISO 7388-1
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Type of product	Threaded copy mill arbor

## Accessories

Pull stud stud sealed, form A suitable for steep tapers 50	308610 50
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
Pull stud Form A suitable for steep tapers 50	308600 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Pull stud 45° sealed suitable for steep tapers 50	308760 50
Torque wrench with reversible ratchet maximum torque 200 Nm	656050 200
Pull stud, 18CrNiMo7 sealed, form B suitable for steep tapers 50	308615 50
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Pull stud sealed suitable for steep tapers 50	308660 50
Pull stud 45° sealed suitable for steep tapers 50	308765 50
Pull stud sealed, form B suitable for steep tapers 50	308620 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308720 50
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50	308820 50

Pull stud sealed, form B suitable for steep tapers 50	308650 50
Special pull stud with internal thread suitable for steep tapers 50	308740 50
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50	308812 50
Pull stud Form B suitable for steep tapers 50	308640 50
Pull stud, 18CrNiMo7 Form A suitable for steep tapers 50	308605 50
Special pull stud with no internal thread sealed suitable for steep tapers 50	308700 50
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Wrench for pull studs ISO 7388 suitable for ISO taper size 50	308830 50