


Garant**Hydraulic clamping chuck BASIC short, slim, Form ADB, SK 40, Clamping range Ø D1: 8 mm****Order data**

Order number	302043 8
GTIN	4062406544324
Item class	31A

Description**Version:**

- **Radial run-out $\leq 3 \mu\text{m}$.**
- **With Balluffchip bore.**
- **Axial length adjustment (adjustment 10 mm) available.**
- **Flexible due to the use of reducing sleeves.**
- **Coolant pressure up to 80 bar.**

Application:

For drilling, reaming and finish milling.

Optional extras:

Back stop screws for direct clamping / use of reducing sleeves on request.

Pull studs (PS) No. 308600 – 308806, PS wrenches No. 308810 – 308830, size 12; 20; 32: Sleeve reducer No. 302135 – 302180.

Machining strategy: HSC

Overhang dimension A: 80.5 mm

Ø D₂: 28 mm

External Ø D: 49.5 mm

Reach L₁: 61.5 mm

L₂: 30 mm

Adjustment travel V: 10 mm

Technical description

Adjustment travel V	10 mm
---------------------	-------

L ₂	30 mm
Overhang dimension A	80.5 mm
Thread M	M6
Reach L ₁	61.5 mm
External Ø D	49.5 mm
Clamping Ø D ₁	8 mm
Ø D ₂	28 mm
Adapter	SK 40
Arbor standard	ISO 7388-1
Shape	ADB
Through-coolant	yes, with max. 80 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Type of product	Hydraulic clamping chuck