



## Slotted reducing adapter, Ø 20 mm, Clamping range Ø D1: 10 mm



### Order data

|              |           |
|--------------|-----------|
| Order number | 302150 10 |
| GTIN         |           |
| Item class   | 33T       |

### Description

#### Version:

**Schunk** GZB-S reducing adapter.

Flexible length pre-setting possible through movable intermediate piece.

**With cooling channel slots.**

#### Application:

- **For drilling, reaming, milling, and tool sharpening.**
- **Very high flexibility due to reduction in clamping diameter.**
- **Very high torque guarantees a higher volume of metal removal compared to direct clamping.**
- **Concentricity  $\pm 5 \mu\text{m}$  (system accuracy at  $3 \times D$ ).**
- **Concentricity  $\pm 2 \mu\text{m}$  (for reducing adapter).**
- **Can be used in all commercially available hydraulic clamping chucks.**

#### Suitable for :

Hydraulic clamping chuck with **clamping Ø 20 mm.**

Ø D: 20 mm

### Technical description

|                           |         |
|---------------------------|---------|
| Clamping Ø D <sub>1</sub> | 10 mm   |
| Ø D                       | 20 mm   |
| External Ø                | 20 mm   |
| Product name attribute    | Ø 20 mm |

|                      |                                      |
|----------------------|--------------------------------------|
| Concentricity system | 5 µm                                 |
| Type of product      | Hydraulic clamping chuck accessories |