

Garant**Shrink-fit chuck with cooling channel bores, SK 30 short, Clamping range Ø D1: 16 mm****Order data**

Order number	302227 16
GTIN	4062406286019
Item class	31A

Description**Version:**

- **High-temperature steel.**
- **Size 3 -5 for carbide, from size 6 for HSS and carbide.**
- **All shanks hard turned (for smooth running!).**
- **With Balluffchip bore.**

With **coolant hole bores** tapped for plugging.

coolant hole bores at clamping Ø D1: 3, 4 and 5 mm cannot be plugged.

Application:

For clamping tools with parallel shank to h6 tolerance.

Suitable for inductive, contact, and hot-air shrink units.

Optional extras:

Pull studs (PS) No. 308600 – 308800. PS wrenches No. 308820 – 308835, Shrink-fit chuck extensions No. 302410 – 302419. Shrink-fit units, accessories No. 354210 – 354450.

Overhang dimension A: 80 mm

External Ø D: 34 mm

Ø D₂: 27 mm

Technical description

Overhang dimension A	80 mm
Ø D ₂	27 mm
Clamping Ø D ₁	16 mm

External Ø D	34 mm
Adapter	SK 30 short
Arbor standard	DIN 69871
Arbor standard	DIN 69871
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Shrink-fit chuck