

**Garant**

**SK shrink-fit chucks slim, with cooling channel bore, SK 40 A = 160, Clamping range  $\varnothing$  D1: 12 mm**


**Order data**

Order number	302336 12
GTIN	4062406243661
Item class	31A

**Description**
**Version:**

- All shanks hard turned (for smooth running!).
- With Balluffchip bore.
- Integral tool length adjustment, range 10 mm available only from size 6 upwards!
- Extra slim design(reduced interference contour).
- With cooling channel bores.

**Application:**

- Cutting operations in tool and mould making.
- For clamping tools with parallel shank to h6 tolerance.

**Optional extras:**

Pull studs (PS) No. 308600 – 308806. PS wrenches No. 308820 – 308835, Shrink-fit chuck extensions No. 302410 – 302419. Shrink-fitting units No. 354210 – 354450.

Cooling channel bore: not pluggable

External  $\varnothing$  D: 33.9 mm

$\varnothing$  D<sub>2</sub>: 18 mm

**Technical description**

External $\varnothing$ D	33.9 mm
Clamping $\varnothing$ D <sub>1</sub>	12 mm
$\varnothing$ D <sub>2</sub>	18 mm
Cooling channel bore	not pluggable

Adapter	SK 40 A = 160
Arbor standard	DIN 69871
Arbor standard	DIN 69871
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HSC
Machining strategy	HPC
Type of product	Shrink-fit chuck