



Combination face mill adaptor, SK 40 A = 52, Spigot Ø d1: 16 mm



Order data

Order number	302505 16
GTIN	4062406110987
Item class	32A

Description

Version:

Internal thread for manual clamping.

Application:

With drive key for milling cutters **with longitudinal groove**, e.g. DIN 841.

With face mill drive ring for milling cutters with **transverse slots**, DIN 1880.

Supplied with:

Drive key, face mill drive ring, and lock screw.

Optional extras:

Special toggle spanner No. 309840.

Concentricity: $\leq 6 \mu\text{m}$

Overall length L: 162 mm

Milling mandrel length L_3 with drive ring: 17 mm

Milling mandrel length L_4 : 27 mm

Thread M: M16

Spare milling cutter lock screw No. 309860: 16

Spare drive ring No. 309870: 16

Technical description

Milling mandrel length L_3 with drive ring	17 mm
Suitable toggle spanner No. 309840	16
Spare milling cutter lock screw No. 309860	16
Overall length L	162 mm

Spare drive ring No. 309870	16
Thread M	M16
Milling mandrel length L ₄	27 mm
Adapter	SK 40 A = 52
Standard	DIN 6358
Arbor standard	DIN 2080
Concentricity	≤ 6 μm
Type of product	Milling cutter spigot