



## Combination face mill adapter, SK 40 A = 52, Spigot Ø d1: 32 mm



### Order data

Order number	302505 32
GTIN	4062406111052
Item class	32A

### Description

#### Version:

Internal thread for manual clamping.

#### Application:

**With drive key** for milling cutters **with longitudinal groove**, e.g. DIN 841.

**With face mill drive ring** for milling cutters with **transverse slots**, DIN 1880.

#### Supplied with:

Drive key, face mill drive ring, and lock screw.

#### Optional extras:

Special toggle spanner No. 309840.

Concentricity:  $\leq 6 \mu\text{m}$

Overall length L: 169 mm

Milling mandrel length  $L_3$  with drive ring: 24 mm

Milling mandrel length  $L_4$ : 38 mm

Thread M: M16

Spare milling cutter lock screw No. 309860 / 309861: 32

Spare drive ring No. 309870: 32

### Technical description

Milling mandrel length $L_3$ with drive ring	24 mm
Milling mandrel length $L_4$	38 mm
Thread M	M16
Overall length L	169 mm

Spare drive ring No. 309870	32
Suitable toggle spanner No. 309840	32
Spare milling cutter lock screw No. 309860 / 309861	32
Adapter	SK 40 A = 52
Standard	DIN 6358
Arbor standard	DIN 2080
Concentricity	$\leq 6 \mu\text{m}$
Type of product	Milling cutter spigot