



Combination face mill adaptor, SK 50 A = 55, Spigot Ø d1: 40 mm



Order data

Order number	302515 40
GTIN	4062406111120
Item class	32A

Description

Version:

Internal thread for manual clamping.

Application:

With drive key for milling cutters **with longitudinal groove**, e.g. DIN 841.

With face mill drive ring for milling cutters with **transverse slots**, DIN 1880.

Supplied with:

Drive key, face mill drive ring, and lock screw.

Optional extras:

Special toggle spanner No. 309840.

Concentricity: $\leq 6 \mu\text{m}$

Overall length L: 209 mm

Milling mandrel length L_3 with drive ring: 27 mm

Milling mandrel length L_4 : 41 mm

Thread M: M24

Spare milling cutter lock screw No. 309860: 40

Spare drive ring No. 309870: 40

Technical description

Overall length L	209 mm
Spare drive ring No. 309870	40
Spare milling cutter lock screw No. 309860	40
Milling mandrel length L_3 with drive ring	27 mm

Suitable toggle spanner No. 309840	40
Milling mandrel length L ₄	41 mm
Thread M	M24
Adapter	SK 50 A = 55
Standard	DIN 6358
Arbor standard	DIN 2080
Concentricity	≤ 6 μm
Type of product	Milling cutter spigot