

**Side lock arbors Form AD, BT 30 short, Clamping range Ø D1: 16 mm****Order data**

|              |               |
|--------------|---------------|
| Order number | 302597 16     |
| GTIN         | 4062406100100 |
| Item class   | 32A           |

**Description****Version:**

All shanks fine bead blasted. Balancing quality G6.3 / 18,000 rpm.

**Application:**

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

**Optional extras:**

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 63 mm

External Ø D: 48 mm

Spare clamping screw No. 30 9900: 16

**Technical description**

|                                  |             |
|----------------------------------|-------------|
| Spare clamping screw No. 30 9900 | 16          |
| External Ø D                     | 48 mm       |
| Overhang dimension A             | 63 mm       |
| Adapter                          | BT 30 short |
| Standard                         | DIN 6359    |
| Arbor standard                   | ISO 7388-2  |
| Arbor standard                   | JIS B6339   |
| Shape                            | AD          |

|                                       |                      |
|---------------------------------------|----------------------|
| Balance quality G at rotational speed | G 6.3 at 18,000 rpm  |
| Concentricity                         | $\leq 3 \mu\text{m}$ |
| Machining strategy                    | HPC                  |
| Type of product                       | Side lock arbor      |

---

## Accessories

|                                                   |           |
|---------------------------------------------------|-----------|
| Pull stud 60° sealed suitable for steep tapers 30 | 308785 30 |
| Pull stud 45° sealed suitable for steep tapers 30 | 308760 30 |
| Pull-stud 60° sealed suitable for steep tapers 30 | 308780 30 |
| Pull stud 45° sealed suitable for steep tapers 30 | 308765 30 |