

Garant
**Side lock arbors Form ADB with cooling channel bores, BT 50 A = 100,
Clamping range \varnothing D1: 8 mm**

Order data

Order number	302655 8
GTIN	4062406100155
Item class	31A

Description
Version:

All shanks hard turned (for smooth running). Balancing quality G2.5 / 25,000 rpm. **With coolant supply holes that can be plugged.**

Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

Optional extras:

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

External \varnothing D: 28 mm

Spare clamping screw No. 30 9900: 8

Technical description

External \varnothing D	28 mm
Spare clamping screw No. 30 9900	8
Adapter	BT 50 A = 100
Standard	DIN 6359
Arbor standard	ISO 7388-2
Arbor standard	JIS B6339
Shape	ADB

Cooling channel bore	lockable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Pull stud 45° sealed suitable for steep tapers 50	308760 50
Pull stud 45° sealed suitable for steep tapers 50	308765 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50	308812 50
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
Wrench for pull studs ISO 7388 suitable for ISO taper size 50	308830 50
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50	308820 50
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Pull-stud 60° sealed suitable for steep tapers 50	308780 50
Spare clamping screw for chucks with clamping Ø D1 8 mm	309900 8