



Boring bar blank Form A, BT 50, A dimension: 315 mm



Order data

| | |
|--------------|---------------|
| Order number | 302891 315 |
| GTIN | 4062406105051 |
| Item class | 32A |

Description

Version:

Taper with collar, hardened and ground. Soft shank for further machining.

Optional extras:

Pull studs (PS) No. 308760 – 308806.

Shape: A

External Ø D: 97 mm

Technical description

| | |
|-----------------|------------------|
| External Ø D | 97 mm |
| Adapter | BT 50 |
| Arbor standard | ISO 7388-2 |
| Arbor standard | JIS B6339 |
| Shape | A |
| Type of product | Boring bar blank |

Accessories

| | |
|--|-----------|
| Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50 | 308810 50 |
|--|-----------|

| | |
|--|-----------|
| Pull-stud 60° sealed suitable for steep tapers 50 | 308780 50 |
| Pull stud 45° sealed suitable for steep tapers 50 | 308760 50 |
| Pull stud 90° sealed suitable for steep tapers 50 | 308795 50 |
| Pull stud 90° sealed suitable for steep tapers 50 | 308790 50 |
| Pull stud 60° sealed suitable for steep tapers 50 | 308785 50 |
| Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50 | 308820 50 |
| Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50 | 308812 50 |
| Pull stud 45° sealed suitable for steep tapers 50 | 308765 50 |
| Wrench for pull studs ISO 7388 suitable for ISO taper size 50 | 308830 50 |