



## Face mill arbor Form A, BT 40 short, Spigot $\varnothing$ d1: 22 mm



### Order data

Order number	303017 22
GTIN	4062406101206
Item class	32A

### Description

#### Version:

Taper shank, spigots, and contact surfaces ground on collar.  
All shanks fine bead blasted. Balancing quality G6.3 / 18,000 rpm. Form A.

#### Supplied with:

Lock screw.

#### Optional extras:

Pull studs (PS) No. 308760 – 308806. Special toggle spanner No. 309840.

Overhang dimension A: 35 mm

External  $\varnothing$  D: 48 mm

Spare milling cutter lock screw No. 309860: 22

### Technical description

External $\varnothing$ D	48 mm
Suitable toggle spanner No. 309840	22
Overhang dimension A	35 mm
Spigot $\varnothing$ d <sub>1</sub>	22 mm
Spare milling cutter lock screw No. 309860	22
Adapter	BT 40 short
Standard	DIN 6357

Arbor standard	JIS B6339
Arbor standard	JIS B6339
Shape	A
Balance quality G at rotational speed	G 6.3 at 18,000 rpm
Concentricity	≤ 5 μm
Machining strategy	HPC
Type of product	Milling head arbor

## Accessories

Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for steep tapers 40 SK	308820 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Torque insert for Pull studs to SO 7388 suitable for steep tapers 40 SK	308812 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Wrench for pull studs ISO 7388 suitable for steep tapers 40 SK	308830 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40

Torque insert for Pull studs to DIN 69872 suitable for steep tapers 40 SK	308810 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40