



Face mill arbor Form A, BT 40 short, Spigot \varnothing d1: 32 mm



Order data

Order number	303017 32
GTIN	4062406101237
Item class	32A

Description

Version:

Taper shank, spigots, and contact surfaces ground on collar.
All shanks fine bead blasted. Balancing quality G6.3 / 18,000 rpm. Form A.

Supplied with:

Lock screw.

Optional extras:

Pull studs (PS) No. 308760 – 308806. Special toggle spanner No. 309840.

Overhang dimension A: 50 mm

External \varnothing D: 78 mm

Spare milling cutter lock screw No. 309860: 32

Technical description

Spigot \varnothing d ₁	32 mm
External \varnothing D	78 mm
Overhang dimension A	50 mm
Spare milling cutter lock screw No. 309860	32
Suitable toggle spanner No. 309840	32
Adapter	BT 40 short
Standard	DIN 6357

Arbor standard	JIS B6339
Arbor standard	JIS B6339
Shape	A
Balance quality G at rotational speed	G 6.3 at 18,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Wrench for pull studs ISO 7388 suitable for steep tapers 40 SK	308830 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for steep tapers 40 SK	308820 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Torque insert for Pull studs to DIN 69872 suitable for steep tapers 40 SK	308810 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Torque insert for Pull studs to SO 7388 suitable for steep tapers 40 SK	308812 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
	308803 40

Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40

Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40

308805 40

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40

308802 40