

Garant**Arbor for screw-in milling cutters with thread, BT 40, Thread M × Usable length L₁: M12X125****Order data**

Order number	303139 M12X125
GTIN	4062406105754
Item class	31A

Description**Version:**

All shanks hard turned.

Application:

To take screw-in milling cutters with thread.

Optional extras:

Pull studs (PS) No. 308760 – 308806.

Machining strategy: HSC

Overhang dimension A: 152 mm

Bore Ø D₁ tolerance IT6: 12.5 mm

Ø D₂: 21 mm

External Ø D: 36 mm

Reach L₁: 125 mm

L₂: 5 mm

Technical description

L ₂	5 mm
Reach L ₁	125 mm
Ø D ₂	21 mm
External Ø D	36 mm
Overhang dimension A	152 mm

Bore Ø D ₁ tolerance IT6	12.5 mm
Adapter	BT 40
Arbor standard	ISO 7388-2
Arbor standard	JIS B6339
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Type of product	Threaded copy mill arbor

Accessories

Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for steep tapers 40 SK	308820 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Torque insert for Pull studs to DIN 69872 suitable for steep tapers 40 SK	308810 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40

Pull stud 90° sealed suitable for steep tapers 40	308795 40
Wrench for pull studs ISO 7388 suitable for steep tapers 40 SK	308830 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Torque insert for Pull studs to SO 7388 suitable for steep tapers 40 SK	308812 40