

Garant
Arbor for screw-in milling cutters with thread, BT 40, Thread M × Usable length L1: M6X75

Order data

| | |
|--------------|---------------|
| Order number | 303139 M6X75 |
| GTIN | 4062406105662 |
| Item class | 31A |

Description
Version:

All shanks hard turned.

Application:

To take screw-in milling cutters with thread.

Optional extras:

Pull studs (PS) No. 308760 – 308806.

Machining strategy: HSC

Overhang dimension A: 102 mm

Bore $\varnothing D_1$ tolerance IT6: 6.5 mm

$\varnothing D_2$: 10 mm

External $\varnothing D$: 23 mm

Reach L_1 : 75 mm

L_2 : 5 mm

Technical description

| | |
|--------------------------------------|--------|
| Reach L_1 | 75 mm |
| L_2 | 5 mm |
| Overhang dimension A | 102 mm |
| External $\varnothing D$ | 23 mm |
| Bore $\varnothing D_1$ tolerance IT6 | 6.5 mm |

| | |
|---------------------------------------|--------------------------|
| Ø D ₂ | 10 mm |
| Adapter | BT 40 |
| Arbor standard | ISO 7388-2 |
| Arbor standard | JIS B6339 |
| Shape | ADB |
| Balance quality G at rotational speed | G 2.5 at 25,000 rpm |
| Concentricity | ≤ 3 µm |
| Machining strategy | HSC |
| Type of product | Threaded copy mill arbor |

Accessories

| | |
|--|-----------|
| Wrench for pull studs ISO 7388 suitable for ISO taper size 40 | 308830 40 |
| Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40 | 308810 40 |
| Pull stud 45° sealed suitable for steep tapers 40 | 308760 40 |
| Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40 | 308820 40 |
| Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40 | 308801 40 |
| Pull stud Hurco 90° with fit sealed suitable for steep tapers 40 | 308806 40 |
| Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40 | 308803 40 |
| Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40 | 308805 40 |
| Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40 | 308812 40 |
| Pull stud 90° sealed suitable for steep tapers 40 | 308795 40 |
| Pull stud 90° sealed suitable for steep tapers 40 | 308790 40 |

| | |
|--|-----------|
| Pull stud Hurco 45° with fit sealed suitable for steep tapers 40 | 308802 40 |
| Pull-stud 60° sealed suitable for steep tapers 40 | 308780 40 |
| Pull stud 45° sealed suitable for steep tapers 40 | 308765 40 |
| Pull stud Hurco 60° with fit sealed suitable for steep tapers 40 | 308804 40 |
| Pull stud 60° sealed suitable for steep tapers 40 | 308785 40 |