

**Side lock arbor, HSK-A 63 A = 160, Clamping range Ø D1: 20 mm****Order data**

Order number	304337 20
GTIN	4062406422202
Item class	32A

Description**Version:**

- **With Balluffchip bore.**
- **HSK mating faces machined.**

Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

External Ø D: 52 mm

Spare clamping screw No. 30 9900: 20

Technical description

Clamping Ø D ₁	20 mm
Spare clamping screw No. 30 9900	20
External Ø D	52 mm
Adapter	HSK-A 63 A = 160
Arbor standard	ISO 12164-1
Arbor standard	DIN 69893
Arbor standard	DIN 69882-4
Shape	A

Balance quality G at rotational speed	G 6.3 at 20,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HPC
Machining strategy	HSC
Type of product	Side lock arbor

Accessories

Spare clamping screw for chucks with clamping $\varnothing$ D1 20 mm	309900 20
--	-----------